

V23105A5478A201 Product Details



V23105A5478A201



Active

Communications / Signal PC Board Relays



[Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- V23105 / D2n Relay Series
- DC Actuating System
- Input Voltage = 48 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Current Rating = 3 Amps.

[View all Features](#) | [Find Similar Products](#)



[Previous](#) [1](#) ... [16](#) [17](#) [18](#) [**19**] [20](#) [Next](#)



Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Compare Products](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [TELECOM AND SIGNAL RELAYS](#) (PDF, English)

Product Specifications:

- [D2n Relay Datasheet](#) (PDF, English)

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Product Photo](#)
- [Schematic](#)
- [PCB Layout](#)
- [Wiring Diagram](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Termination Type = Through Hole
- Comment = BT47 Type / Specification T4563C (current tested)

Electrical Characteristics:

- Actuating System= DC
- Input Voltage (VDC) = 48
- Contact Current Rating (Amps.) = 3
- [Coil Resistance \(?\)](#) = 4000
- Coil Power, Nominal (mW) = 575
- Dielectric Between Coil and Contacts (V rms) = 1000

Body Related Features:

- [Series](#) = V23105 / D2n Relay
- Polarized = No

Contact Related Features:

- Mounting Options = PC Board
- Enclosure = Immersion Cleanable
- [FCC Part 68 Isolation](#) = Yes
- Approved Standards = CSA Certified, UL Recognized
- Contact Material = Silver Nickel, Gold Overlay
- Approx. Dimensions (L x W x H) (mm[in]) = 20.30 x 10.10 x 11.40 [.800 x .398 x .450]
- Contact Type = Single
- Pin Configuration = DIP

Configuration Related Features:

- [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- [Coil Magnetic System](#) = Non Polarized, Monostable
- Coil Suppression Diode = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240C, Wave solder capable to 260C, Wave solder capable to 265C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Other:

- Brand = Axicom

