

## Power Extension Cord, NEMA 5-15P to NEMA 5-15R - Heavy-Duty, 15A, 120V, 14 AWG, 25 ft. (7.62 m), Black

MODEL NUMBER: P024-025



25 ft. extension cord connects your computer or other device with a NEMA 5-15P plug to a PDU or UPS with a NEMA 5-15R outlet.

### Features

**Heavy-Duty Extension Cable for Network Devices That Require a Heavy-Gauge Connection** This 25-ft. (7.62 m) extension cord features 14 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. It can be used to connect a computer, monitor, printer or other device with a NEMA 5-15P plug to a wall outlet, PDU, surge protector or UPS system with a NEMA 5-15R outlet. The 25-ft. (7.62 m) length allows you great flexibility in placing equipment with respect to the power outlet.

### Highlights

- Recommended for powering computers, printers and other home/office peripherals
- 25-ft. (7.62 m) length allows great flexibility in placing devices in relationship to AC outlet
- Ideal replacement for worn-out or missing 25-ft. (7.62 m) extension cord

### Applications

- Connect devices like computers, servers and monitors to a PDU in your data center
- Extend an existing power connection up to 25-ft. (7.62 m) to more easily place a device or reach a power source in a rack
- Provide a high-quality replacement for a worn-out or missing power cord

### Package Includes

- P024-025 25-ft. (7.62 m) Extension Cord, NEMA 5-15P to NEMA 5-15R, Black

## Specifications

| OVERVIEW                    |                                                   |
|-----------------------------|---------------------------------------------------|
| UPC Code                    | 037332197160                                      |
| Device Compatibility        | Computer; Monitor/HDTV; Printer; Server; UPS; PDU |
| Country/Region              | North America                                     |
| INPUT                       |                                                   |
| Maximum Input Amps          | 15                                                |
| Voltage Compatibility (VAC) | 125                                               |
| CONNECTIONS                 |                                                   |
| Side A - Connector 1        | NEMA 5-15P                                        |
| Side B - Connector 1        | NEMA 5-15R                                        |



Powering Business Worldwide

TRIPP LITE  
SERIES

| PHYSICAL                           |                             |
|------------------------------------|-----------------------------|
| Plug Color                         | Black                       |
| Cable Jacket Color                 | Black                       |
| Cable Jacket Material              | PVC                         |
| Cable Jacket Rating                | VW-1                        |
| Power Cord Jacket Type             | SJT                         |
| Cable Outer Diameter (OD)          | 9.3mm                       |
| Number of Conductors               | 3                           |
| Wire Gauge (AWG)                   | 14                          |
| Wire Gauge (OD - mm <sup>2</sup> ) | 2.08                        |
| Cable Length (ft.)                 | 25                          |
| Cable Length (m)                   | 7.62                        |
| Cable Length (cm)                  | 762.00                      |
| Shipping Dimensions (hwd / in.)    | 14.17 x 11.80 x 0.50        |
| Shipping Dimensions (hwd / cm)     | 35.99 x 29.97 x 1.27        |
| Shipping Weight (lbs.)             | 2.46                        |
| Shipping Weight (kg)               | 1.12                        |
| ENVIRONMENTAL                      |                             |
| Operating Temperature Range        | -4° to 140°F (-20° to 60°C) |
| Storage Temperature Range          | -4° to 140°F (-20° to 60°C) |
| Operating Humidity Range           | 10% to 65% RH               |
| Storage Humidity Range             | 10% to 65% RH               |
| FEATURES & SPECIFICATIONS          |                             |
| Antibacterial                      | No                          |
| Angled Plug                        | No                          |
| High Voltage                       | No                          |
| Locking Plug                       | No                          |
| Coiled Power Cord                  | No                          |
| STANDARDS & COMPLIANCE             |                             |
| Product Certifications             | cUL Listed; UL Listed       |
| Product Compliance                 | RoHS                        |
| WARRANTY & SUPPORT                 |                             |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                        |                           |
|----------------------------------------|---------------------------|
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty |
|----------------------------------------|---------------------------|

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.