

## Power Cord, C19 to NEMA L5-20P - Heavy-Duty, 20A, 125V, 12 AWG, 10 ft. (3.05 m), Black

MODEL NUMBER: P045-010



Heavy-duty extension cord transforms a C20 plug into a locking NEMA L5-20P plug and extends an existing connection up to 10 ft.

### Features

**Heavy-Duty Extension Cable Connects Devices That Require a Heavy-Gauge Connection** This heavy-duty extension cord features 12 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. This C19 to L5-20P cord transforms a non-locking plug into a locking plug and can be used to connect a high-output device to a wall outlet or a PDU or UPS with L5-20R outlets. It is also a recommended replacement or upgrade of a standard power cord provided by the device's manufacturer. The 10-ft. (3.05 m) length allows you great flexibility in placing equipment with respect to the power outlet.

**Locking L5-20P Connector Helps Prevent Accidental Disconnection and Expensive Downtime** Having a cable come loose accidentally can mean the loss of power and costly downtime. The locking connector helps you avoid such danger, protecting critical equipment by maintaining a secure link without failure. The locking cable is also invaluable when moving equipment in a rack or removing equipment from tight areas, ensuring the power cord always stays connected.

### Highlights

- 10-ft. (3.05 m) length allows great flexibility in placing devices in relationship to AC outlet
- Heavy-duty cable replaces or upgrades standard power cord provided by manufacturer
- Thick 12 AWG wire gauge manages high power levels required for larger equipment
- Locking connector maintains secure link to avoid loss of power and costly downtime

### Applications

- Connect devices to a power outlet up to 10-ft. (3.05 m) away in your office or workspace
- Transform a non-locking C20P plug into a locking L5-20P plug to prevent a power loss due to accidental disconnection
- Extend an existing power connection up to 10-ft. (3.05 m) to more easily place a device or reach a power source in a rack
- Update or replace the standard power cord provided by a device's original manufacturer

### Package Includes

- P045-010 C19 to L5-20P Heavy-Duty Extension Cord, 10-ft. (3.05 m), Black

## Specifications

| OVERVIEW                    |                  |
|-----------------------------|------------------|
| UPC Code                    | 037332140937     |
| Device Compatibility        | Server; UPS; PDU |
| Country/Region              | North America    |
| INPUT                       |                  |
| Maximum Input Amps          | 20               |
| Voltage Compatibility (VAC) | 125              |



Powering Business Worldwide

TRIPP LITE  
SERIES

| CONNECTIONS                        |                               |
|------------------------------------|-------------------------------|
| Side A - Connector 1               | NEMA L5-20P                   |
| Side B - Connector 1               | IEC-320-C19                   |
| PHYSICAL                           |                               |
| Color                              | Black                         |
| Plug Color                         | Black                         |
| Cable Jacket Color                 | Black                         |
| Cable Jacket Material              | PVC                           |
| Cable Jacket Rating                | VW-1                          |
| Power Cord Jacket Type             | SJT                           |
| Cable Outer Diameter (OD)          | 11mm                          |
| Number of Conductors               | 3                             |
| Wire Gauge (AWG)                   | 12                            |
| Wire Gauge (OD - mm <sup>2</sup> ) | 3.31                          |
| Cable Length (ft.)                 | 10                            |
| Cable Length (m)                   | 3.05                          |
| Shipping Dimensions (hwd / in.)    | 10.98 x 7.00 x 0.50           |
| Shipping Dimensions (hwd / cm)     | 27.89 x 17.78 x 1.27          |
| Shipping Weight (lbs.)             | 1.72                          |
| Shipping Weight (kg)               | 0.78                          |
| ENVIRONMENTAL                      |                               |
| Operating Temperature Range        | -4° to 140°F (-20° to 60°C)   |
| Storage Temperature Range          | -4° to 140°F (-20° to 60°C)   |
| Relative Humidity                  | 10% to 65% RH, Non-Condensing |
| FEATURES & SPECIFICATIONS          |                               |
| Antibacterial                      | No                            |
| Angled Plug                        | No                            |
| High Voltage                       | No                            |
| Locking Plug                       | No                            |
| Coiled Power Cord                  | No                            |
| STANDARDS & COMPLIANCE             |                               |
| Product Certifications             | cUL Listed; UL Listed         |
| Product Compliance                 | RoHS                          |

WARRANTY & SUPPORT

|                                        |                           |
|----------------------------------------|---------------------------|
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty |
|----------------------------------------|---------------------------|

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.