

Heavy-Duty PDU Power Cable, C13 to C14 - 15A, 250V, 14 AWG, Green, 6 ft. (1.83 m)

MODEL NUMBER: P005-006-GN



Computer power cord extends your existing C13-to-C14 power connection as much as 6 feet.

Features

Power Cable for Network Devices That Require a Heavy-Gauge Connection This 14 AWG C14-to-C13 computer power cord is appropriate for high power connections and a dependable solution for server applications that demand a higher-rated, heavier-gauge cable. You can use this computer power cable for connecting a server, hard drive, monitor or computer to a PDU or USB system. It's a worthy upgrade or replacement for the power cable that came included with your device. At 6-ft. (1.83 m), the P005-006-GN gives you some flexibility in placing your connected devices.

Green Connectors for Fast, Easy ID That Can Save Costly Downtime This 6-ft. (1.83 m) computer power cable features fully molded green C14 and C13 connectors. This allows you to color-code your connection in a crowded workstation or rack, helping you quickly identify it and prevent an accidental disconnection.

Highlights

- Ideal for powering your server, computer or other network component
- PDU power cable upgrades or replaces the manufacturer's standard computer power cord
- 14 AWG construction designed to handle high power levels needed for powering large equipment
- Green connectors allow quick identification in a crowded workstation or rack
- 6-ft. (1.83 m) power cable gives you flexibility in placing your devices away from an outlet

Applications

- Connect a computer, server, hard drive or display to a PDU or UPS up to 6-ft. (1.83 m) away
- Replace or update the standard power cable provided by your device's original manufacturer
- Extend an existing power connection up to 6-ft. (1.83 m) to more easily place a device or reach a power source in a rack

Package Includes

- P005-006-GN Heavy-Duty Power Cable, Green, 6-ft. (1.83 m)

Specifications

OVERVIEW	
UPC Code	037332168368
Device Compatibility	Computer; Monitor/HDTV; Printer; Server; Router; Network Switch; UPS; PDU
Country/Region	Global
INPUT	
Maximum Input Amps	15
Voltage Compatibility (VAC)	100-250
CONNECTIONS	
Side A - Connector 1	IEC-320-C14



Powering Business Worldwide



Side B - Connector 1	IEC-320-C13
PHYSICAL	
Plug Color	Green
Cable Jacket Color	Black
Cable Jacket Material	PVC
Cable Jacket Rating	FT2
Power Cord Jacket Type	SJT
Cable Outer Diameter (OD)	9.2mm
Number of Conductors	3
Wire Gauge (AWG)	14
Wire Gauge (OD - mm ²)	2.08
Cable Length (ft.)	6
Cable Length (m)	1.83
Shipping Dimensions (hwd / in.)	10.00 x 7.10 x 0.50
Shipping Dimensions (hwd / cm)	25.40 x 18.03 x 1.27
Shipping Weight (lbs.)	0.71
Shipping Weight (kg)	0.32
ENVIRONMENTAL	
Operating Temperature Range	-4 TO 140 F (- 20° TO 60°C)
Storage Temperature Range	-4 TO 140 F (- 20° TO 60°C)
Operating Humidity Range	20-80% RH
Storage Humidity Range	20-80% RH
FEATURES & SPECIFICATIONS	
Angled Plug	No
High Voltage	Yes
Locking Plug	No
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.