

MOSFET – Single P-Channel, POWERTRENCH[®], 1.8 V Specified

FDMA291P

General Description

This device is designed specifically for battery charge or load switching in cellular handset and other ultraportable applications. It features a MOSFET with low on-state resistance. The MicroFET[™] 2x2 package offers exceptional thermal performance for its physical size and is well suited to linear mode applications.

Features

- 6.6 A, –20 V
 - $R_{DS(ON)} = 42 \text{ m}\Omega @ V_{GS} = -4.5 \text{ V}$
 - $R_{DS(ON)} = 58 \text{ m}\Omega @ V_{GS} = -2.5 \text{ V}$
 - $R_{DS(ON)} = 98 \text{ m}\Omega @ V_{GS} = -1.8 \text{ V}$
- Low Profile – 0.8 mm Maximum – in the New Package MicroFET 2x2 mm
- Free from Halogenated Compounds and Antimony Oxides
- This Device is Pb-Free, Halide Free and RoHS Compliant RoHS Compliant


ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted.)

Symbol	Parameter	Value	Unit
V_{DS}	Drain–Source Voltage	–20	V
V_{GS}	Gate–Source Voltage	±8	V
I_D	Drain Current – Continuous (Note 1a) – Pulsed	–6.6 24	A
P_D	Power Dissipation for Single Operation (Note 1a) (Note 1b)	2.4 0.9	W
T_J, T_{STG}	Operating and Storage Junction Temperature Range	–55 to +150	°C


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS


Symbol	Parameter	Value	Unit
$R_{\theta JC}$	Thermal Resistance, Junction–to–Case	13	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction–to–Ambient (Note 1a)	52	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction–to–Ambient (Note 1b)	145	°C/W



WDFN6 (MicroFET 2 x 2)
CASE 511CZ



MARKING DIAGRAM



&Z = Assembly Plant Code
 &2 = 2 Digit Date Code (YW)
 &K = 2 Digit Lot Traceability Code
 291 = Specific Device Code

ORDERING INFORMATION

Device	Package	Shipping [†]
FDMA291P	WDFN6 (Pb-Free)	3000 / Tape & Reel

[†]For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, [BRD8011/D](#).

FDMA291P

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted.)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
--------	-----------	-----------------	-----	-----	-----	------

OFF CHARACTERISTICS

B _V DSS	Drain–Source Breakdown Voltage	V _{GS} = 0 V, I _D = –250 μA	–20	–	–	V
ΔB _V DSS / ΔT _J	Breakdown Voltage Temperature Coefficient	I _D = –250 μA, Referenced to 25°C	–	–12	–	mV/°C
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = –16 V, V _{GS} = 0 V	–	–	–1	μA
I _{GSS}	Gate–Body Leakage	V _{GS} = ±8 V, V _{DS} = 0 V	–	–	±100	nA

ON CHARACTERISTICS (Note 2)

V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = –250 μA	–0.4	–0.7	–1.0	V
ΔV _{GS(th)} / ΔT _J	Gate Threshold Voltage Temperature Coefficient	I _D = –250 μA, Referenced to 25°C	–	3	–	mV/°C
R _{DS(on)}	Static Drain–Source On–Resistance	V _{GS} = –4.5 V, I _D = –6.6 A V _{GS} = –2.5 V, I _D = –5.1 A V _{GS} = –1.8 V, I _D = –3.9 A V _{GS} = –4.5 V, I _D = –6.6 A, T _J = 125°C	– – –	36 51 79	42 58 98	mΩ
g _{FS}	Forward Transconductance	V _{DS} = –5 V, I _D = –6.6 A	–	16	–	S

DYNAMIC CHARACTERISTICS

C _{ISS}	Input Capacitance	V _{DS} = –10 V, V _{GS} = 0 V, f = 1.0 MHz	–	1000	–	pF
C _{OSS}	Output Capacitance		–	190	–	pF
C _{RSS}	Reverse Transfer Capacitance		–	100	–	pF

SWITCHING CHARACTERISTICS (Note 2)

t _{d(on)}	Turn–On Delay Time	V _{DD} = –10 V, I _D = –1 A, V _{GS} = –4.5 V, R _{GEN} = 6 Ω	–	13	23	ns
t _r	Turn–On Rise Time		–	9	18	ns
t _{d(off)}	Turn–Off Delay Time		–	42	68	ns
t _f	Turn–Off Fall Time		–	25	40	ns
Q _g	Total Gate Charge	V _{DS} = –10 V, I _D = –6.6 A, V _{GS} = –4.5 V	–	10	14	nC
Q _{gs}	Gate–Source Charge		–	2	–	nC
Q _{gd}	Gate–Drain Charge		–	3	–	nC

DRAIN–SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS

I _S	Maximum Continuous Drain–Source Diode Forward Current		–	–	–2	A
V _{SD}	Drain–Source Diode Forward Voltage	V _{GS} = 0 V, I _S = –2 A (Note 2)	–	–0.8	–1.2	V
t _{rr}	Reverse Recovery Time	I _F = –6.6 A dI _F /d t = 100 A/μs	–	20	–	ns
Q _{rr}	Reverse Recovery Charge		–	8	–	nC


Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

NOTES:

- R_{θJA} is determined with the device mounted on a 1 in² pad 2 oz copper pad on a 1.5 x 1.5 in. board of FR–4 material. R_{θJC} is guaranteed by design while R_{θJA} is determined by the user's board design.



a. 52 °C/W when mounted on
a 1 in² pad of 2 oz copper



b. 145 °C/W when mounted on
a minimum pad of 2 oz copper

- Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.

TYPICAL CHARACTERISTICS




Figure 1. On-Region Characteristics




Figure 2. On-Resistance Variation with Drain Current and Gate Voltage




Figure 3. On-Resistance Variation with Temperature.




Figure 4. On-Resistance Variation with Gate-to-Source Voltage




Figure 5. Transfer Characteristics




Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature

TYPICAL CHARACTERISTICS (Continue)




Figure 7. Gate Charge Characteristics




Figure 8. Capacitance Characteristics




Figure 9. Maximum Safe Operating Area




Figure 10. Single Pulse Maximum Power Dissipation








Figure 11. Transient Thermal Response Curve


Thermal characterization performed using the conditions described in Note1b.
Transient thermal response will change depending on the circuit board design.

WDFN6 2x2, 0.65P
CASE 511CZ
ISSUE O

DATE 31 JUL 2016



RECOMMENDED
LAND PATTERN OPT 1



RECOMMENDED
LAND PATTERN OPT 2

NOTES:

- A. PACKAGE DOES NOT FULLY CONFORM TO JEDEC MO-229 REGISTRATION
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 2009.
- D. LAND PATTERN RECOMMENDATION IS EXISTING INDUSTRY LAND PATTERN.

DOCUMENT NUMBER:	98AON13614G	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	WDFN6 2X2, 0.65P	PAGE 1 OF 1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales