

# Bridge Rectifiers, 0.5 A

## MB1S-MB8S


### Description

The MB family of bridge rectifiers is a 0.5 A rectifier family that achieves high surge current absorption within a very small foot print. Within its small 35 mm<sup>2</sup> form factor, the MB family shines in its surge capability. In order to absorb high surge currents, the design supports a 35 A I<sub>FSM</sub> rating and a 5.0 A<sup>2</sup>Sec I<sup>2</sup>T rating. Devices in the family are also rated to breakdown voltages of up to 1000 V. These features make the MB family ideal for small power supplies that need a little extra surge capability.

For higher I<sub>FAV</sub> current ratings, lower profile packaging, or lower V<sub>F</sub> values, explore the **onsemi** MDB family of bridge rectifiers. For improved V<sub>F</sub> and efficiency values in the MB package or even higher surge capability, ask about **onsemi**'s pending MBxSV family.


### Features

- Low-Leakage
- Surge Overload Rating: 35 A peak
- Ideal for Printed Circuit Board
- UL Certified: UL #E258596
- This Device is Pb-Free and RoHS Compliant



SOIC4 W  
CASE 751EP

### MARKING DIAGRAM



|      |                                   |
|------|-----------------------------------|
| \$Y  | = Logo                            |
| &Z   | = Assembly Plant Code             |
| &3   | = 3-Digit Data Code (Year & Week) |
| MB*S | = Specific Device Code            |
| *    | = 1/2/4/6/8                       |

### ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

# MB1S–MB8S

## ABSOLUTE MAXIMUM RATINGS

(Values are at  $T_A = 25^\circ\text{C}$  unless otherwise noted)

| Symbol      | Parameter                                                                  | MB1S        | MB2S | MB4S | MB6S | MB8S | Unit             |
|-------------|----------------------------------------------------------------------------|-------------|------|------|------|------|------------------|
| $V_{RRM}$   | Maximum Repetitive Reverse Voltage                                         | 100         | 200  | 400  | 600  | 800  | V                |
| $V_{RMS}$   | Maximum RMS Bridge Input Voltage                                           | 70          | 140  | 280  | 420  | 560  | V                |
| $V_R$       | DC Reverse Voltage (Rated $V_R$ )                                          | 100         | 200  | 400  | 600  | 800  | V                |
| $I_{F(AV)}$ | Average Rectified Forward Current at $T_A = 50^\circ\text{C}$              | 0.5         |      |      |      |      | A                |
| $I_{FSM}$   | Non-Repetitive Peak Forward Surge Current:<br>8.3 ms Single Half-Sine-Wave | 35          |      |      |      |      | A                |
| $T_{STG}$   | Storage Temperature Range                                                  | -55 to +150 |      |      |      |      | $^\circ\text{C}$ |
| $T_J$       | Operating Junction Temperature Range                                       | -55 to +150 |      |      |      |      | $^\circ\text{C}$ |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

## THERMAL CHARACTERISTICS

| Symbol          | Parameter                                                 | Value | Unit                      |
|-----------------|-----------------------------------------------------------|-------|---------------------------|
| $P_D$           | Power Dissipation                                         | 1.4   | W                         |
| $R_{\theta JA}$ | Thermal Resistance, Junction to Ambient, per Leg (Note 1) | 85    | $^\circ\text{C}/\text{W}$ |
| $R_{\theta JL}$ | Thermal Resistance, Junction to Lead, per Leg (Note 1)    | 20    | $^\circ\text{C}/\text{W}$ |

1. Device mounted on PCB with  $0.5 \times 0.5$  inch ( $13 \times 13$  mm) lead length.

## ELECTRICAL CHARACTERISTICS (Values are at $T_A = 25^\circ\text{C}$ unless otherwise noted)

| Symbol | Parameter                               | Conditions                   | Value | Unit                 |
|--------|-----------------------------------------|------------------------------|-------|----------------------|
| $V_F$  | Forward Voltage, per Bridge             | $I_F = 0.5$ A                | 1.0   | V                    |
| $I_R$  | Reverse Current, per Leg at Rated $V_R$ | $T_A = 25^\circ\text{C}$     | 5.0   | $\mu\text{A}$        |
|        |                                         | $T_A = 125^\circ\text{C}$    | 0.5   | mA                   |
| $I^2t$ | $I^2t$ Rating for Fusing                | $t < 8.3$ ms                 | 5.0   | $\text{A}^2\text{s}$ |
| $C_T$  | Total Capacitance, per Leg              | $V_R = 4.0$ V, $f = 1.0$ MHz | 13    | pF                   |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

## ORDERING INFORMATION

| Part Number | Top Mark | Package              | Shipping <sup>†</sup> |
|-------------|----------|----------------------|-----------------------|
| MB1S        | MB1S     | SOIC4 W<br>(Pb-Free) | 3,000 / Tape & Reel   |
| MB2S        | MB2S     |                      |                       |
| MB4S        | MB4S     |                      |                       |
| MB6S        | MB6S     |                      |                       |
| MB8S        | MB8S     |                      |                       |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 1. Derating Curve for Output Rectified Current




Figure 2. Typical Reverse Leakage Characteristics Per Leg




Figure 3. Maximum Non-Repetitive Peak Forward Surge Current Per Leg




Figure 4. Typical Junction Capacitance Per Leg







Figure 5. Typical Forward Voltage Characteristics Per Leg

**SOIC4 W**  
**CASE 751EP**  
**ISSUE O**

DATE 30 SEP 2016



OPTION A - BEVEL EDGE



NOTES: UNLESS OTHERWISE SPECIFIED

- A. THIS PACKAGE DOES NOT CONFORM TO JEDEC TO269AA
- B. ALL DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH AND TIE BAR EXTRUSIONS.
- D. DIMENSIONS AND TOLERANCES AS PER ASME Y14.5-2009.
- E. LAND PATTERN AS PER IPC7351# SOIC254P960X400-4N

|                         |                    |                                                                                                                                                                                     |
|-------------------------|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON13753G</b> | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SOIC4 W</b>     | <b>PAGE 1 OF 1</b>                                                                                                                                                                  |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)