

SML0606-RGB-TR

Super Red/Green/Super Blue
Surface Mount LED
1.6 × 1.5 × 0.4mm Chip LED
120° Viewing Angle

DWG BY:
BL / GP
09-02-09

CHK BY:
PL
06-25-18

R&D:
KS
06-25-18

MFG:
LD
06-25-18

QA:
EE
06-25-18

REVISION LTR: B
ECR#: 062518-GP01
06-25-18


● Features:

1. Emitted Color : Super Blue, Green and Super Red.
2. Lens Appearance: Water Clear.
3. Multi-color type.
4. 1.6x1.5x0.4mm(0605) standard package
5. Suitable for all SMT assembly methods.
6. Compatible with infrared and vapor phase reflow solder process.
7. Compatible with automatic placement equipment.
8. This product doesn't contain restriction Substance, comply ROHS standard.

● Applications:

1. Backlighting: LCDs, Key pads advertising.
2. Status indicators: Consumer & industrial electronics.
3. General use.

● Package Dimensions:



NOTES:

1. All dimensions are in millimeters.
2. Tolerance is ± 0.10 mm unless otherwise specified.
3. Specifications are subject to change without notice.

● Absolute Maximum Ratings(Ta=25°C)







Parameter	Symbol	Super Blue	Green	Super Red	Unit
Power Dissipation	Pd	70	70	50	mW
Forward Current	I _F	20	20	20	mA
Peak Forward Current * 1	I _{FP}	100	100	100	mA
Reverse Voltage	V _R	5			V
Operating Temperature	Topr	-40°C~+85°C			-
Storage Temperature	Tstg	-40°C~+85°C			-
Soldering Temperature	Tsol	See Page 7			-

* 1 Condition for I_{FP} is pulse of 1/10 duty and 0.1msec width.


● **Electrical and optical characteristics(Ta=25°C)**

Parameter	Symbol	Condition	Color	Min.	Typ.	Max.	Unit
Forward Voltage	V _F	I _F =5mA	Super Red Green Super Blue	-	2.0 2.8 2.8	2.4 3.2 3.2	V
Luminous Intensity	I _v	I _F =5mA	Super Red Green Super Blue	18.5 63 28	40 120 63	-	mcd
Reverse Current	I _R	V _R =5V	Super Red Green Super Blue	- - -	- - -	100 1 1	μA
Peak Wave Length	λ _p	I _F =5mA	Super Red Green Super Blue	- - -	630 520 460	-	nm
Dominant Wave Length	λ _d	I _F =5mA	Super Red Green Super Blue	615 520 465	- - -	625 535 475	nm
Spectral Line Half-width	Δλ	I _F =5mA	Super Red Green Super Blue	-	20 30 30	-	nm
Viewing Angle	2θ _{1/2}	I _F =5mA	Super Red Green Super Blue	-	120	-	deg
Chromaticity Coordinates	X	I _F =5mA	Super Red	-	-	-	
	Y			-	-	-	
Chromaticity Coordinates	X	I _F =5mA	Green	-	-	-	
	Y			-	-	-	
Chromaticity Coordinates	X	I _F =5mA	Super Blue	-	-	-	
	Y			-	-	-	

● Typical Electro-Optical Characteristics Curves



● Tapping and packaging specifications(Units: mm)



NOTE: 3000 pcs PER REEL

● **Bin Limits**

Intensity Bin Limits (B5) (5mA)

BIN CODE	Min. (mcd)	Max. (mcd)
M	28	42
N	42	63
P	63	94
Q	94	140

Tolerance for each Bin limit is $\pm 15\%$.

Color Bin Limits (B5) (5mA)

BIN CODE	Min.(nm)	Max.(nm)
4	465	470
5	470	475

Tolerance for each Bin limit is $\pm 1\text{nm}$.

V_F Bin Limits (B5) (5mA)

BIN CODE	Min.(v)	Max.(v)
E	2.4	2.6
F	2.6	2.8
G	2.8	3.0
H	3.0	3.2

Tolerance for each Bin limit is $\pm 0.05\text{V}$.

Intensity Bin Limits (GK) (5mA)

BIN CODE	Min. (mcd)	Max. (mcd)
Q	94	140
R	140	210
S	210	317
T	317	475

Tolerance for each Bin limit is $\pm 15\%$.

● **Bin Limits**

Color Bin Limits (GK) (5mA)

BIN CODE	Min.(nm)	Max.(nm)
6	520	525
7	525	530
8	530	535

Tolerance for each Bin limit is $\pm 1\text{nm}$.

V_F Bin Limits (GK) (5mA)

BIN CODE	Min.(v)	Max.(v)
E	2.4	2.6
F	2.6	2.8
G	2.8	3.0
H	3.0	3.2


Tolerance for each Bin limit is $\pm 0.05\text{V}$.

Intensity Bin Limits (JE)(5mA)

BIN CODE	Min. (mcd)	Max. (mcd)
L	18.5	28
M	28	42
N	42	63
P	63	94

Tolerance for each Bin limit is $\pm 15\%$.

● **BIN : X X X-X X X-X**



● **Reliability Test**

Classification	Test Item	Reference Standard	Test Conditions	Result
Endurance Test	Operation Life	MIL-STD-750D:1026 MIL-STD-883D:1005 JIS-C-7021 :B-1	Ta: Under room temperature Test time:1,000hrs IF=Product Recommended IF	0/32
	High Temperature High Humidity Storage	MIL-STD-202F:103B JIS-C-7021 :B-11	Ta:85±5°C RH:90%-95% Test time:240hrs	0/32
	High Temperature Storage	MIL-STD-883:1008 JIS-C-7021 :B-10	Ta:100±5°C Test time:1,000hrs	0/32
	Low Temperature Storage	JIS-C-7021 :B-11	Ta: -40±5°C Test time=1,000hrs	0/32
Environmental Test	Temperature Cycling	MIL-STD-202F:107D MIL-STD-750D:1051 MIL-STD-883D:1010 JIS-C-7021 :A-2	Ta:-35±5°C~25±5°C~85±5°C~25±5°C 30min 5min 30min 5min	0/32
	Thermal Shock	MIL-STD-202F:107D(1980) MIL-STD-750D:1051(1995) MIL-STD-883D:1011(1991)	Ta:-40±5°C ~+85±5°C 10min 10 min Time: 20min/cycle 10cycle	0/32
	Wetting balance	MIL-STD-883:2003 MIL-STD-202F:208D MIL-STD-883D:2003	Ta:230±5°C Time:5±0.5s	0/32
	Solder Resistance	MIL-STD-202F:210A MIL-STD-883D:1011 JIS-C-7021 :A-1	Ta:260±10°C Time:10±1s	0/32


● **Judgment criteria of failure for the reliability**

Measuring items	Symbol	Measuring conditions	Judgement criteria for failure
Forward voltage	V _F (V)	I _F =5mA	Initial Level*1.1
Reverse current	I _R (uA)	V _R =5V	Over U*2
Luminous intensity	I _v (mcd)	I _F =5mA	Initial Level*0.7

Note: 1.U means the upper limit of specified characteristics.

2.Measurment shall be taken between 2 hours and after the test pieces have been returned to normal ambient conditions after completion of each test.

● **IR-Reflow Soldering**



1. Avoid any external stress applied to the resin while the LEDs are at high temperature, especially during soldering .
2. Avoid rapid cooling or any excess vibration during temperature ramp-down process
3. Although the soldering condition is recommended above, soldering at the lowest possible temperature is feasible for the LEDs

● **IRON Soldering**

350°C Within 3 sec.,One time only.

● Notes for designing:

Care must be taken to provide the current limiting resistor in the circuit so as to drive the LEDs within the rated figures. Also, caution should be taken not to overload LEDs with instantaneous voltage at the turning ON and OFF of the circuit.

When using the pulse drive care must be taken to keep the average current within the rated figures. Also, the circuit should be designed so as to be subjected to reverse voltage when turning off the LEDs.

● Storage:

In order to avoid the absorption of moisture, it is recommended to solder LEDs as soon as possible after unpacking the sealed envelope.

If the envelope is still packed, to store it in the environment as following:

- (1) Temperature : 5°C -30°C (41°F) Humidity : RH 60% Max.
- (2) After this bag is opened, devices that will be applied to infrared reflow, vapor-phase reflow, or equivalent soldering process must be:
 - a. Completed within 168 hours.
 - b. Stored at less than 30% RH.
- (3) Devices require baking before mounting, if:
 - (2) a or (2) b is not met.
- (4) If baking is required, devices must be baked under below conditions:
48 hours at 60°C±3°C.

● Package and Label of Products:

- (1) Package: Products are packed in one bag of 3000 pcs (one taping reel) and a label is attached on each bag.