SPDIF Digital Coaxial or Toslink Optical to Stereo RCA Audio Converter

Product ID: SPDIF2AA



The SPDIF2AA Toslink/Optical SPDIF to RCA Audio Converter lets you convert a 2-channel Digital Coaxial or Toslink/Optical SPDIF input signal into an RCA analog stereo output.

Perfect for home and professional audio applications, this SPDIF to RCA audio converter saves the cost of upgrading equipment for compatible connections, and offers separate Digital Coax and Toslink inputs for dual-function conversion. The small form factor design makes it suitable for installation into virtually any location, regardless of space constraints, while still providing a lossless audio signal. Plus, the digital coaxial or Toslink to RCA converter supports plug-and-play installation, saving you time and hassle.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

• Connect newer Blu-Ray, DVD Players and Game Consoles to two channel analog stereo receivers

• Convert or extend your digital audio input into an analog format, without signal or quality loss

Features

• Accepts Digital Coax or Toslink digital audio input

- Outputs analog L/R RCA stereo analog audio
- Compact form factor
- Easy to install and use
- 24-bit S/PDIF incoming bit stream

General		
	UPC	065030832304
	Package Quantity	1
	Warranty	2 Years

Power		
	Power Source	AC Adapter Included
	Input Voltage	100 - 240 AC
	Input Current	0.4 A
	Output Voltage	5 DC
	Output Current	2
	Center Tip Polarity	Positive
	Plug Type	N
	Power Consumption	10

Physical & Environmental		
	Color	Black
	Material	Steel
	Product Length	2.0 in [52.0 mm]
	Product Width	1.7 in [42.0 mm]
	Product Height	1.0 in [25.4 mm]
	Weight of Product	2.5 oz [70 g]
	Operating Temperature	0C to 70C (32F to 158F)
	Storage Temperature	-10C to 80C (14F to 176F)

	Humidity	10~85 % RH Non-Condensing
Hardware		
	AV Input	Digital Coaxial
		Toslink
	AV Output	RCA Audio
Packaging & In-the-Box		
	Included in Package	1 - SPDIF to RCA converter
		1 - universal power adapter (NA, EU, UK, ANZ)
		1 - instruction manual
	Package Width	5.6 in [14.4 cm]
	Package Depth	6.9 in [17.5 cm]
	Package Height	1.6 in [41 mm]
	Shipping (Package) Weight	10.1 oz [286 g]
Connector(s)		
	Connector 1 (Quantity)	1
	Connector 1	TOSLINK (Optical S/PDIF)
	Connector 2 (Quantity)	1
	Connector 2	RCA (S/PDIF Coaxial Audio)
	Connector 3 (Quantity)	1
	Connector 3	RCA (Stereo Audio)

Product appearance and specifications are subject to change without notice.