

Kellems Wire Management, Cord
Connectors, Straight Male, 1.50-1.63", 1 1/2",
Aluminum

By Hubbell Wiring Device-Kellems
Catalog # [SHC1062](#)

Kellems Wire Management, Cord Connectors, Straight Male, 1.50-1.63",
1 1/2", Aluminum

Features

- Cast aluminum cord connector, one-piece design with machined threads
- Lock nuts sold separately
- UL514B Tray cable rated for dry locations

Application

Straight Male- Form 6

Performance

Environmental - Hazardous Locations - Used in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 in accordance with the NEC, Environmental - Operating Temperatures - -30°F to +240°F (-34°C to +115°C)

Specifications

Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Nylon Washer Between Box And Fitting.
Nema Rating	NEMA Type 4, 4X, 12 and 13
Industry Standard(s)	UL Listed

Conductor

Number Of Conductors	Single
Conductor Range	1.5-1.63 in (38.1- 41.3 mm)

Dimensions



Hub Size	1-1/2 "
Display Size	1 1/2" NPT

General

Series	Standard Duty Series
OEM Brand Name	Hubbell Wiring Device-Kellems
Specifications	• Cord Diameter Range Inches (mm) - 1.50"-1.63" (38.1-41.3) • Material - Cast Aluminum • NPT Hub Size - 1 1/2 Inch
UPC	783585200620
Type	Straight Male
Material - Mounting Hardware	Locknut or Tapped Opening
Item Type	Cord Connectors
Material	Aluminum, Cast

Logistics

Carton Quantity	10
-----------------	----

Operational

Temperature Rating	Minimum -30 Deg F to 240 Deg F (-34 Deg C to 115 Deg C)
--------------------	---

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[English\]](#)