

[My Cart](#)[My Part Lists](#)[Sign In/Register](#)[English \(Change\)](#)

Search by Keyword or Part #

**SMD030F-2 Product Details****SMD030F-2**

TE Internal Number: RF0314-000

[Active](#)**PolySwitch Resettable Devices**[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)**Product Highlights:**

- Surface Mount Application
- Vmax Operating = 60 V
- Vmax = 60 V
- Imax = 10 A
- Family Name = SMD

[View all Features](#)**Quick Links**

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#)[Request Sample](#)[Find Similar Products](#)[Buy Product](#)**Documentation & Additional Information****Product Drawings:**

- None Available

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)**Product Type Features:**

- UL File Number = E74889
- CSA File Number = CA78165

Electrical Characteristics:

- [Vmax Operating \(V\)](#) = 60
- Vmax (V) = 60
- Imax (A) = 10
- [IH \(Room Temperature\) \(A\)](#) = 0.3
- [IT \(Room Temperature\) \(A\)](#) = 0.60
- [Rmin \(Ω\)](#) = 1.20
- [R1 Max \[Post Trip\] \(Ω\)](#) = 4.80
- Power Dissipation (Max) (W) = 1.7

Termination Related Features:

- Construction = Surface Mount

Contact Related Features:

- [Family Name](#) = SMD

Configuration Related Features:

- [Form Factor \(inches\)](#) = 2920
- [Form Factor \(mm\)](#) = 7555

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant
- TUV Certificate No. = R72041427

Conditions for Usage:

- [Operating Temperature \(Max.\) \(°C\)](#) = 85

Operation/Application:

- Application = Surface Mount

Packaging Related Features:

- Packaging Method = Tape & Reel

Other:

- Brand = Raychem

**Corporate Information**[Who We Are](#)[Investors](#)[News Room](#)[Supplier Portal](#)[Careers](#)**Quick Links**[Check Distributor Inventory](#)[Cross Reference](#)[Find Documents & Drawings](#)[Product Compliance Support Center](#)[Site Map](#)**Customer Support**[Email or Chat with Us](#)[Find a Phone Number](#)[Search Knowledge Base](#)[Manage Your Account](#)**Sign up for our eNewsletter**

Enter your email address

Follow Us On:

Twitter Facet Flickr Linke YouTi

Visit Us On: